

# Bridge Alert Management System

**Totem  
BAMS**

Totem Bridge Alert Management System (BAMS) presents bridge alarms and warnings on one central panel. Silence and Acknowledge of all bridge alarms can be done from one location.


**SAFETY FIRST – Let the Navigator do the Navigation !**



## Main advantages:

- Silence and Acknowledge in one central location – no more running around the bridge.
- Easy view of Bridge equipment status in one glance.
- History Log of all Bridge alarms allows better preventive maintenance.

## SYSTEM DIAGRAM



## Features

- Display on the BAMS monitor of all alarms from various bridge sources
- Enables silence of audible alarms from the BAMS touch screens
- Acknowledge of alarms using two-way communication with other bridge systems
- One year log of all system events (system ON/OFF, fault resets, alarm log, user activity log, etc.)
- Download of log files to external media (via USB)
- If alarm description or related information is available then BAMS shows the information content and allows acknowledgment from the BAMS panel
- Can interface with 24 serial input channels, 50 digital inputs and 8 digital outputs
- BAMS can be operated in 3 different modes: Sea mode (default), Silent mode (no audible alarms) or Anchor mode (alert if position drifted etc.). The system can be integrated (option) with Totem Bridge Navigational Watch Alarm System (BNWAS)
- Optional - several monitoring stations
- Optional – integrated with BNWAS

**Type approved by DNV-GL in accordance with latest IMO resolutions:  
MSC.302(87); MSC.252(83); IEC61924 ed.2; A.694(17); MSC.1021(26)**



**TotemPlus**  
Where Shipping Meets High-Tech